

## INDUSTRIAL FORKLIFT TYRES

- Premium tyre, designed for heavy duty service on forklift trucks, material handling & mining equipment.
- The deep tread, extra thick sidewalls & tough casing provide exceptional durability & minimize the risk of punctures & accidental damages.
- Silica & natural rubber in tread compound provides greater chip and rear resistance.
- Specially designed rim guard ensures protection against flats & wheel damages in the rim flange area



SIZE	PATTERN	PLY RATING	RIM WIDTH 	TYPE	SECTION WIDTH 		OVERALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	studs	kg	lbs	bar	psi		kmph	mph
4.80/4.00-8	LIFTKING HD	8	3.0	TT	117	4.6	414	16.3	8	10	530	1165	10.0	145	86	A6/30 kmph	A6/20 mph
5.70/5.00-8		10			132	5.2	467	18.3	14	18	1400	3080	9.8	142	120		
6.90/6.00-9		10	4.0		160	6.3	540	21.2	16	20	1700	3740	8.3	120	126		
6.50-10		12	5.0		178	7.0	588	23.1	16	20	2180	4796	8.8	128	135		
7.00-12		14	5.0		192	7.6	690	27.1	18	23	2725	5995	8.8	128	143		
7.00-15		12	5.5		201	7.9	762	30.0	18	23	3075	6765	8.6	125	147		
7.50-15		14	6.0		211	8.3	772	28.3			3000	6600	9.0	130	146		
28x9-15		14	7.0		213	8.4	720	33.7			3875	8525	9.8	142	155		
8.25-15		16	6.5		239	9.4	855	33.6			3550	7810	9.1	131	152		

## INDUSTRIAL FORKLIFT TYRES

- **ROCK PLUS HD** - Deep tread, extra thick sidewall & tough casing ensure longer life. silica & natural rubber base compound provides greater chip & tear resistance.



**ROCK PLUS HD**

SIZE	PATTERN	PLY RATING	RIM WIDTH  inch	TYPE	SECTION WIDTH 		OVERALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	mm/s	kg	lbs	bar	psi		kmph	mph
250-15	ROCKPLUS HD	20	7.0/7.5	TT	240	9.4	735	28.9	19	24	5000	11000	10.0	145	164	A6/30 kmph	A6/20 mph
300-15		20	8.0		300	11.8	840	33.1	23	29	6500	14300	9.0	128	173	A6/30 kmph	A6/20 mph
10.00-20		18	7.5		284	11.2	1080	42.5	31	39	6500	14300	8.3	120	173	A8/40 kmph	A8/25 mph
12.00-20		20	8.5		320	12.6	1151	45.3	35	44	7750	17050	9.0	130	179	A6/30 kmph	A6/20 mph

## INDUSTRIAL FORKLIFT TYRES

- Unique lug design for extra surface for highest mileage.
- Cuts and cracks resistant tread compound.



**LIFTPOWER**

SIZE	PATTERN	PLY RATING	RIM WIDTH  inch	TYPE	SECTION WIDTH 		OVERALL DIAMETER 		NSD		LOAD CAPACITY 		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	mm/s	kg	lbs	bar	psi		kmph	mph
23x5	LIFTPOWER	10	4.0	TT	155	6.1	635	25.0	10	13	2000	4400	8.0	114	132	A6/30 kmph	A6/20 mph

\* All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Speedways Rubber Company or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Speedways Rubber Company and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Speedways Rubber Company.