

TRUCK TYRES



 **SPEEDWAYS**
TYRES
...Keeps You Moving

- **Designed for Durability and Performance.**
- **Strong Casing.**
- **Excellent Retreadability.**



MILESTONE

TRUCK & LIGHT TRUCK TYRES (DOT)

- Better traction and good braking performance.
- Ensures even wear.
- Low heat generation.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
LT205/90D15 (7.00-15E)	10	5.5	TL	206	8.1	770	30.3	1180	2600	4.5	65	114	P/150 kmph	P/94 mph
LT225/90D16 (7.50-16E)	10	6.0	TL	218	8.6	823	32.4	1590	3500	5.5	80	124	P/150 kmph	P/94 mph



LOAD RUNNER

TRUCK & LIGHT TRUCK TYRES

- Longer life with stable performance.
- High load carrying capacity.
- Strong casing.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
9.00-16	16	6.5	TT	254	10.0	914	36.0	2120	4664	7.2	105	134	J/100 kmph	J/60 mph
	18							2360	5190	7.6	110		148	A8/40 kmph
10.00-20	16	7.5	TT	274	10.8	1075	42.3	3000	6600	7.9	115	146	J/100 kmph	J/60 mph
	18							3075	6765	8.3	120		147	J/100 kmph



MILEAGE MAKER

TRUCK & LIGHT TRUCK TYRES (DOT)

- Balanced rib type design.
- Excellent retreadability.
- Ensure even wear.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inchi	mm	inchi	kg	lbs	bar	psi		kmph	mph
7.00-15	12	5.5	TT	206	8.1	770	30.3	1180	2596	6.2	90	114	3/100 kmph	3/60 mph
9.00-20	14	7.0	TT	259	10.2	1025	40.3	2575	5665	7.6	110	141	3/100 kmph	3/60 mph



LOAD KING

TRUCK & LIGHT TRUCK TYRES (DOT)

- Designed for durability and performance.
- Strong casing.
- Higher skid depth.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inchi	mm	inchi	kg	lbs	bar	psi		kmph	mph
7.50-16	16	6.0	TT	218	8.6	823	32.4	1600	3520	7.6	110	124	3/100 kmph	3/60 mph
	18							1650	3630	7.9	115	125	3/100 kmph	3/60 mph
8.25-16	16	6.5	TT	231	9.1	841	33.1	1850	4070	7.6	110	129	3/100 kmph	3/60 mph
	18							1900	4180	7.9	115	130	3/100 kmph	3/60 mph
9.00-20	16	7.0	TT	259	10.2	1035	40.7	2650	5830	7.9	115	142	3/100 kmph	3/60 mph
	18							2725	5995	8.2	119	143	3/100 kmph	3/60 mph



MILESTONE

TRUCK & LIGHT TRUCK TYRES

- Even tread wear and superior mileage.
- Wet rolling resistant and good road grip.
- Excellent traction and braking.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
6.40-15	8	4.0	TT	160	6.3	693	27.3	710	1562	4.2	60	96	3/100 kmph	3/60 mph
	10							825	1815	5.4	77	101	3/100 kmph	3/60 mph
6.70-15	8	4.5	TT	165	6.5	710	28.0	825	1815	4.2	60	101	3/100 kmph	3/60 mph
	10							925	2035	5.4	77	105	3/100 kmph	3/60 mph
7.00-15	12	5.5	TT	206	8.1	770	30.3	1180	2596	6.2	90	114	3/100 kmph	3/60 mph
7.50-15	12	6.0	TT	216	8.5	780	30.7	1360	2990	5.5	80	119	3/100 kmph	3/60 mph
	14							1450	3190	6.2	90	121	3/100 kmph	3/60 mph
7.00-16	10	5.5	TT	206	8.1	785	30.9	1090	2398	5.1	73	111	3/100 kmph	3/60 mph
	12							1215	2675	6.2	90	115	3/100 kmph	3/60 mph
	14							1320	2904	6.9	100	118	3/100 kmph	3/60 mph
7.50-16	12	6.0	TT	218	8.6	823	32.4	1400	3080	6.2	90	120	3/100 kmph	3/60 mph
	14							1500	3300	6.9	100	122	3/100 kmph	3/60 mph
8.25-16	14	6.5	TT	231	9.1	841	33.1	1800	3960	6.9	100	128	3/100 kmph	3/60 mph
	16							1850	4070	7.6	110	129	3/100 kmph	3/60 mph
10.00-20	16	7.5	TT	274	10.8	1060	41.7	3000	6600	7.9	115	146	3/100 kmph	3/60 mph
11.00-20	16	8.0	TT	290	11.4	1082	42.6	3250	7150	7.9	115	149	3/100 kmph	3/60 mph



SAMRAT+

TRUCK & LIGHT TRUCK TYRES

- Longer life and stable performance.
- Better air circulation and faster heat dissipation.
- High load carrying capacity.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
9.00-16	16	6.5	TT	254	10.0	914	36.0	2120	4664	7.2	105	134	3/100 kmph	3/60 mph
	18							2475	6600	7.2	105	140	3/100 kmph	3/60 mph



TIGER

TRUCK & LIGHT TRUCK TYRES

- Longer tyre life thanks to better tread contact area.
- High load carrying capacity.
- Low heat generation.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.00-15	12	5.5	TT	206	8.1	770	30.3	1180	2596	6.2	90	114	3/100 kmph	3/60 mph
10.00-20	18	7.5	TT	274	10.8	1075	42.3	3075	6765	8.3	120	147	3/100 kmph	3/60 mph



GTSW

TRUCK & LIGHT TRUCK TYRES

- Unique design with high mileage.
- Better air circulation and faster heat dissipation.
- High fuel efficiency.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.50-16	16	6.0	TT	218	8.6	823	32.4	1600	3520	7.6	110	124	3/100 kmph	3/60 mph
	18							1650	3630	7.9	115	125	3/100 kmph	3/60 mph
8.25-16	14	6.5	TT	231	9.1	841	33.1	1800	3960	6.9	100	128	3/100 kmph	3/60 mph
	16							1850	4070	7.6	110	129	3/100 kmph	3/60 mph



SAND GRIP

TRUCK & LIGHT TRUCK TYRES

- Superior tread and shoulder design.
- Better tyre life and uniform wear
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.50-16	16	6.0	TT	218	8.6	823	32.4	1600	3520	7.6	110	124	J/100 kmph	J/60 mph
	18							1650	3630	7.9	115			
12.00-20	18	8.5	TT	320	12.6	1138	44.8	3250	7150	7.3	105	149	G/90 kmph	G/56 mph



LOAD POWER

TRUCK & LIGHT TRUCK TYRES

- Premium compound helps in reducing heat generation.
- Better tyre life and fuel efficiency.
- Irregular wear resistant.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
12.00-24	18	8.5	TT	315	12.3	1240	48.8	4250	9350	7.9	115	158	J/100 kmph	J/60 mph



HUNTER

TRUCK & LIGHT TRUCK TYRES

- Strong casing.
- Ensure even wear.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
5.60-14	10	4.0	TT	145	5.7	640	25.2	580	1276	4.3	61	89	3/100 kmph	3/60 mph



SILVER STONE

TRUCK & LIGHT TRUCK TYRES

- Irregular wear resistant.
- Better tyre life and fuel efficiency.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
6.00-16	10	4.5	TT	174	6.9	752	29.6	875	1925	5.1	73	103	3/100 kmph	3/60 mph
6.50-16	12	4.5	TT	185	7.3	765	30.1	1030	2266	4.7	68	109	3/100 kmph	3/60 mph



TOUGH TRACK PLUS

TRUCK & LIGHT TRUCK TYRES

- Unique tread design.
- High fuel efficiency.
- Low heat generation.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
6.00-16	10	4.0	TT	174	6.9	752	29.6	875	1925	5.1	73	103	110/100 kmph	110/60 mph



RANGER

TRAILER TYRES

- Irregular wear resistant.
- Wet rolling resistant.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
4.50-10	8	3.5	TT	132	5.2	490	19.3	520	1145	5.0	72	86	F/80 kmph	F/50 mph
	10	3.5	TT	125	4.9	490	19.3	560	1232	5.0	73	88	F/80 kmph	F/50 mph
5.00-10	8	3.5	TT	135	5.3	510	20.0	580	1276	5.0	72	89	F/80 kmph	F/50 mph
	10	3.5	TT	155	6.1	531	20.9	615	1353	5.1	73	91	F/80 kmph	F/50 mph
145-10	8	3.5	TT	140	5.5	500	19.7	500	1100	4.5	65	84	F/80 kmph	F/50 mph
4.50-12	8	3.0	TT	127	5.0	544	21.4	290	640	2.4	35	65	L/120 kmph	L/75 mph
	325							715	2.8	40	69	L/120 kmph	L/75 mph	
4.80-12	6	3.8	TT	127	5.0	526	20.7	450	990	6.3	89	80	L/120 kmph	L/75 mph
5.00-12	10	3.5	TT	142	5.6	564	22.3	500	1100	4.3	61	84	L/120 kmph	L/75 mph



STORM

TRAILER TYRES

- Balanced rib type design.
- Excellent traction and braking.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
6.00-14	8	4.5	TT	170	6.7	681	26.8	690	1818	4.3	61	95	J/100 kmph	J/60 mph
	10							800	1760	5.0	72	100	J/100 kmph	J/60 mph
6.50-14	8	4.5	TT	180	7.1	704	27.7	850	1870	4.3	62	102	J/100 kmph	J/60 mph
	10							925	2035	4.5	65	105	J/100 kmph	J/60 mph
E78-14	6	5.5	TT	188	7.4	656	25.8	620	1364	2.2	31	91	A8/40 kmph	A8/25 mph
175D-14	6	5.0	TT	178	7.0	656	25.8	615	1353	3.1	41	91	A8/40 kmph	A8/25 mph



SULTAN

TRAILER TYRES

- Strong casing.
- High fuel efficiency.
- Good road grip.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
4.80-8	6	3.8	TT	122	4.8	420	16.5	335	737	6.3	89	70	F/80 kmph	F/50 mph
5.70-8	8	4.5	TT	150	5.9	467	18.3	488	1074	7.1	100	83	F/80 kmph	F/50 mph



IAP

TRAILER TYRES

- Even tread wear and superior mileage.
- Longer life with stable performance.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.50-10	10	5.5	TT	206	8.1	645	25.3	1360	2992	6.2	90	119	A8/40 kmph	A8/25 mph
8.25-10	12	6.0	TT	211	8.3	675	26.5	1650	3630	7.2	105	125	A8/40 kmph	A8/25 mph



MILESTONE +

TRAILER TYRES

- Even tread wear and superior mileage.
- Wet rolling resistant and good road grip.
- Excellent traction and braking.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
5.30-12	6	4.3	TT	135	5.3	550	21.6	475	1045	5.6	79	82	L/120 kmph	L/75 mph
5.65-12	4	4.0	TT	140	5.5	520	20.5	250	550	1.7	24	60	L/120 kmph	L/75 mph
145D-12	8	4.0	TT	140	5.5	540	21.2	375	825	2.3	32	74	L/120 kmph	L/75 mph
155D-12	8	4.5	TT	155	6.1	558	22.0	560	1230	3.6	51	82	K/110 kmph	K/68 mph
	10	4.5	TT	155	6.1	558	22.0	625	1375	6.3	89	92	K/110 kmph	K/68 mph
5.90-15	8	4.0	TT	150	5.9	670	26.4	460	1012	2.0	28	81	A8/40 kmph	A8/25 mph
195/80D-15	8	5.5	TT	195	10.0	697	27.4	775	1705	4.2	60	99	A8/40 kmph	A8/25 mph



DUST STORM

TRAILER TYRES

- Even tread wear and superior mileage.
- Longer life with stable performance.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
9.00-15	8	6.5	TT	254	10.0	865	34.0	1100	2420	3.5	50	112	A8/40 kmph	A8/25 mph
9.00-16	8	6.5	TT	254	10.0	898	35.3	1210	2662	3.5	50	115	A8/40 kmph	A8/25 mph



TRACKGRIP

TRAILER TYRES

- High load carrying capacity.
- Irregular wear resistant.
- Low heat generation.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
215/75-17.5	12	6.8	TT	213	8.4	780	30.7	2120	4664	7.0	100	134	A8/40 kmph	A8/25 mph
	16	6.8	TT	213	8.4	780	30.7	2650	5830	9.0	128	142	A8/40 kmph	A8/25 mph
225/75-17.5	16	6.8	TT	224	8.8	795	31.3	2900	6380	9.0	128	145	A8/40 kmph	A8/25 mph
235/75-17.5	16	6.8	TT	236	9.3	810	31.9	3400	7480	9.0	128	151	A8/40 kmph	A8/25 mph



MILLENNIUM

TRAILER / JEEP TYRES

- Reinforced sidewalls to enhance protection against impacts and cuts from obstacles and debris.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
F78-15	6	5.5	TT	198	7.8	694	27.3	760	1672	3.5	50	98	A8/40 kmph	A8/25 mph



LANDMARK

VINTAGE VEHICLE TYRES

- Built to last and provide long service life.
- Irregular wear resistant.
- Ensure even wear.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
5.60-13	6	4.0	TT	155	6.1	595	23.4	385	847	2.8	40	75	A8/40 kmph	A8/25 mph
1.65D-13	6	4.5	TT	165	6.5	596	23.5	475	1045	2.8	40	82	A8/40 kmph	A8/25 mph



SAMRAT

VINTAGE VEHICLE TYRES

- Built to withstand rough terrain, heavy loads and harsh conditions.
- Better tyre life and fuel saving.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
5.00-19	6	3.0	TT	135	5.3	746	29.3	670	1474	3.8	54	94	A8/40 kmph	A8/25 mph
6.00-19	8	3.6	TT	160	6.3	800	31.5	925	2035	4.2	60	105	A8/40 kmph	A8/25 mph
7.00-19	10	5.0	TT	193	7.6	860	33.8	1360	2992	5.2	74	119	A8/40 kmph	A8/25 mph
	12							1450	3190	5.4	76	121	A8/40 kmph	A8/25 mph
8.00-19	10	5.0	TT	221	8.7	910	35.8	1650	3630	5.2	74	125	A8/40 kmph	A8/25 mph



MILITARY

MILITARY JEEP OFFROAD 4x4 TYRES

- Excellent for ON/OFF Road applications and ensures good all-round performance as well as good traction and durability in ON/OFF Road applications.
- Each tyre features bias belted construction for superior strength and impact resistance, these tyres are built to handle the toughest Off-Road conditions on the planet.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference ± 2.5 %		Load Capacity		Inflation Pressure		Load Index	SPEED		
				mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph	
6.00-16	8	4.5	TT	168	6.6	752	29.6	330	13.0	2184	86.0	690	1518	4.2	60	95	G/90 kmph	G/56 mph	
7.00-16	8	5.5	TT	196	7.7	785	30.9	366	14.4	2362	93.0	975	2145	3.8	40	107	G/90 kmph	G/56 mph	
7.50-16	8	6.0	TT	221	8.7	825	32.5	374	14.7	2393	94.2	1090	2376	4.2	61	111	G/90 kmph	G/56 mph	
	12											1250	2750	6.2	90	116	G/90 kmph	G/56 mph	
9.00-16	8	6.5	TT	244	9.6	905	35.6	424	16.7	2768	109.0	1360	2990	3.4	50	119	G/90 kmph	G/56 mph	
	14											1650	3630	6.2	90	125	G/90 kmph	G/56 mph	
8.25-20	10	6.0	TT	234	9.2	925	36.4	389	15.3	2483	97.8	1600	3520	5.1	73	124	G/90 kmph	G/56 mph	
7.50-20	8	6.0	TT	208	8.2	930	36.6	432	17.0	2692	106.0	1450	3190	5.0	72	121	G/90 kmph	G/56 mph	
	14											1775	3905	7.3	105	128	G/90 kmph	G/56 mph	
9.00-20	12	7.5	TT	259	10.2	1034	40.7	483	19.0	3124	123.0	2060	4532	6.0	85	133	G/90 kmph	G/56 mph	
10.00-20	12	7.5	TT	284	11.2	1080	42.5	508	20.0	3175	125.0	2180	4790	5.1	73	135	G/90 kmph	G/56 mph	
12.00-20	18	8.5	TT	320	12.6	1138	44.8	524	20.6	3360	132.3	3250	7150	7.3	105	149	G/90 kmph	G/56 mph	
12.00-24										UNDER DEVELOPEMENT									
14.00-24	16	10.0	TT	375	14.8	1350	53.1	610	24.0	4013	158.0	3650	8030	3.8	54	153	A8/40 kmph	A8/25 mph	



GTSW

MILITARY JEEP OFFROAD 4x4 TYRES

- Aggressive tread pattern provides maximum traction on various terrains.
- Reinforced sidewalls to enhance protection against impacts and cuts from obstacles and debris.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference ± 2.5 %		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.50-16	8	6.0	TT	218	8.6	823	32.4	374	14.7	2393	94.2	1120	2664	4.2	60	112	G/90 kmph	G/56 mph



ML-999

MILITARY JEEP OFFROAD 4x4 TYRES

- Built to last and provide long service life.
- Designed for all season use providing excellent performance in various weather conditions.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width Inch	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference ± 2.5 %		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
145-12M	4	4.0	TT	145	5.7	561	22.1	260	10.2	1646	65.0	400	880	3.7	45	76	E/70 kmph	E/44 mph



SAND GRIP

MILITARY JEEP OFFROAD 4x4 TYRES

- Built to withstand rough terrain, heavy loads and harsh conditions.
- Typically constructed with high strength materials to resist punctures, tears and damage.
- Excellent retreadability.

SIZE	Ply Rating	Rim Width Inch	TYPE	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circumference ± 2.5 %		Load Capacity		Inflation Pressure		Load Index	SPEED	
				mm	inch	mm	inch	mm	inch	mm	inch	kg	lbs	bar	psi		kmph	mph
7.50-16	12	6.0	TT	221	8.7	825	32.5	374	14.7	2393	94.2	1180	2596	5.1	73	114	B/50 kmph	B/30 mph
12.00-20	18	8.5	TT	320	12.6	1138	44.8	524	20.6	3360	132.3	3250	7150	7.3	105	149	G/90 kmph	G/56 mph